

## UV-Meter Black Standard x10 Series

- + UV intensity  $mW/cm^2$
- + high sensitivity
- + big 4 digit display
- + 2 channel x1/x10
- + probe type sensor



The UV-Meter Black Standard x10 is a high quality UV measuring instrument.

All measurements are expressed in  $mW/cm^2$  in order to compare light sources or to check uniformity of the light emission.

Typical application fields are the control of units for the exposure of diazo, polymer, chromaline and daylight films in the graphic arts industry, suntan equipment, sterilisation units and other fields of photo biology.

The UV-Meter Black Standard x10 is available in various six different measuring ranges\*:  
(Please state upon order)

6.4.1 UV-Meter Black Standard x10 Diazo	350 – 460 nm
6.4.2 UV-Meter Black Standard x10 UV-A	315 – 400 nm
6.4.2.1 UV-Meter Black Standard x10 UV-LED	380 – 420 nm
6.4.3 UV-Meter Black Standard x10 UV-B	280 – 315 nm
6.4.4 UV-Meter Black Standard x10 UV-C	230 – 280 nm
6.4.5 UV-Meter Black Standard x10 Full UV	230 – 410 nm
6.4.6 UV-Meter Black Standard x10 UV-V	395 – 445 nm

\*further spectral ranges available upon request

The display readings are fictitiously. The basic setting is done by means of a potentiometer.

### Technical Data:

Max. Power input :	sensor input 1.000 $mW/cm^2$
Wavelength:	315 – 400 nm UV-A (or other)
Temperature:	0 - 45 C
Display:	4 Digits
Range X 1 :	0,01 – 19,99 $mW/cm^2$
Range X 10 :	0,1 – 199,9 $mW/cm^2$
Weight:	approx. 200 grams
Battery:	1 x 9 V Block Battery
Dimensions:	140 mm x 75 mm x 24 mm
Sensor cable:	1 meter
Sensor Ø	40 mm x 10 mm
Base Accuracy:	± 5 %

The probe-type sensor of the UV-Meter can withstand max. 110° C / 230° F for up to 10 seconds. The temperature of the housing should not exceed 45° C / 113° F.

### Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Re-calibration will also be necessary after change of battery. Ongoing, PTB traceable calibration with certificate

Subject to change without prior notice © 2014-01

UV-DESIGN (Office)  
Triebstrasse 3  
63636 Brachtal  
GERMANY  
Tel.: +49 (0)6053 619824  
Fax: +49 (0)6053 619820

(Office & Workshop) UV-DESIGN  
Fabrikstrasse 12  
63636 Brachtal  
GERMANY  
Tel.: +49 (0)6053 8095431  
Fax: +49 (0)6053 8095433