

UV-T Integrator SQUARE

special LED versions available

- + extra flat 10 mm / .4 inches
- + UV-intensity mW/cm²
- + UV-dose mJ/cm²
- + Permanent or triggered recording*
- + LCD display
- + temperature °C/°F
- + SD Memory Card (option)
- + graphical and numerical display on a PC (option)
- + re-chargeable accu cell
- + further spectral ranges upon request
- + available up to 20W/cm²
- + available with high speed sampling rate 0.0007s (1400/s)



The UV-T Integrator SQUARE is a self-contained, high quality UV measuring instrument. It is designed to measure and display peak UV intensity, UV dosage and temperature in the UV curing process.

In the standard version it is equipped with one UV sensor and one temperature sensor for the measuring of:

Full UV 230 – 410 nm
Temp 32 to 230° F / 0 to 110° C

With this total UV band peak intensity and dose measuring plus the extra temperature measuring, many of the measuring requirements of UV curing applications can be covered.

Due to its UV sensor and the integrated microprocessor the UV-T Integrator SQUARE can measure and display the peak UV-intensity of the total UV spectrum (mW/cm²).

Additionally, this UV-Integrator is calculating the UV-dosage (mJ/cm²) of the UV energy supplied during the time of exposure of one measuring cycle. The UV-dosage is calculated as the total Integral of UV-dosage over the full UV spectral bands.

Additionally it is measuring temperatures from 32 to 230° F / 0 to 110° C.

*This Integrator features a selectable „triggered mode“, i.e. the 30 sec recording cycle starts within a 120 second readiness phase not before the incident UV-intensity exceeds 2 mW/cm².

The sensors are on the back of the unit which also serves as a heat shield. After completion of the measuring cycle the measuring results can be scrolled through on the built in 2 x 16 digit LCD display.

A special AUTO-OFF feature that turns off the unit automatically after one minute serves as energy saving and extension of the battery service life.

This microprocessor integrator can optionally be equipped with an SD Memory Card Slot. All measuring data are stored and can be downloaded to a computer. The special evaluation software allows to show, edit and store a history of the measuring results of the entire measuring cycle as graphic and numeric charts (mW/cm²) and (mJ cm²) and temperature (°C/°F)

The UV-T Integrator SQUARE is available in six different measuring ranges*:

(Please state upon order)

Item 51.2.3.1 UV-T Integrator SQUARE, Type 1 Diazo	350 – 460 nm
Item 51.2.3.2 UV-T Integrator SQUARE, Type 2 UV-A	315 – 410 nm
Item 51.2.3.3 UV-T Integrator SQUARE, Type 3 UV	230 – 410 nm
Item 51.2.3.4 UV-T Integrator SQUARE, Type 4 UV-B	280 – 315 nm
Item 51.2.3.5 UV-T Integrator SQUARE, Type 5 UV-C	230 – 280 nm
Item 51.2.3.6 UV-T Integrator SQUARE, Type 6 UV-V	395 – 445 nm

*further spectral ranges available upon request

Subject to change without prior notice © 2009-01

UV-DESIGN (Office)
Triebstrasse 3
63636 Brachtal
GERMANY
Tel.: +49 (0)6053 619824
Fax: +49 (0)6053 619820

(Office & Workshop) UV-DESIGN
Fabrikstrasse 12
63636 Brachtal
GERMANY
Tel.: +49 (0)6053 8095431
Fax: +49 (0)6053 8095433

UV-T Integrator SQUARE

Technical Data:

Spectral range:	UV 230 – 410 nm (Standard)
Max. Power Input	0 to 5,000 mW/cm ²
Display:	LCD, 2x16 digits
Display range:	0 to 36,000 mJ/cm ²
Measuring range:	0 to 2,000 mW/cm ²
Sampling rate:	0.01 sec (100/sec)
Recording cycle:	90 sec.
Readiness phase:	120 sec.
Power source:	3.7 V LiPO Accu
Power consumption:	20 μ A
Accu service life:	1,000 charging cycles
Dimensions:	80 mm x 80 mm x 22 mm (3" x 3" x 7/8")
Weight:	approx. 10 ounce (300 g)
Operating temperature:	32 to 113° F / 0 to 45° C
Heat protection:	Heat shield on back plate
Base Accuracy:	\pm 5 %

While on the conveyer belt, the UV-T Integrator SQUARE can withstand max. 230° F / 110° C for up to 10 seconds. The temperature of the housing should not exceed 113° F / 45° C. Because of uneven radiation distribution of the UV light source and different type of construction of the measuring devices by different manufacturers, different readings may appear under the same measurement conditions.

Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Re-calibration will also be necessary after change of battery. Ongoing, PTB traceable calibration with certificate

***also available up to 20W/cm², display resolution in relation to maximum wattage**
***also available with high speed sampling rate 0.0007s(1400/s)**

Subject to change without prior notice © 2014-01

Optional Feature:

Stores data on SD-Memory Card for the download of data to a Computer

